


ADF[®]-Rohrmanschette

Pipe sleeves for construction waterproofing



Material number	Width, article	Material strength	Contents	Packaging	Colour
205966001	35 cm	approx. 0.65 mm	1 piece	piece	Grey with SCHOMBURG logo

Product features

- Tear-resistant
- Particularly stretchy
- watertight
- Bitumen-compatible

Advantages

- With prefabricated hopper for connection work
- Highly flexible and stretchy
- Bitumen-compatible
- Reliability through prefabrication

Fields of application / waterproofing

- For the watertight waterproofing of pipe penetrations
- Suitable for pipe diameter DN 100 to DN 150
- System component of ADF[®]-Dehnfugenband (Expansion-Joint-Tape)

Technical Data

Material properties

Product components	Piece goods
Base material	Composite material: Fleece-membrane-fleece
Diameter (internal)	approx. 90 mm
For pipe diameter	approx. 100 - 125 mm
Vapour diffusion behaviour	Vapour permeable

Application

Consumption	1 pc per application
-------------	----------------------

ADF[®]-Rohrmanschette

Application technology

Aids/tools

- Flat trowel
- Pressure roller

Substrate preparation

Requirement for substrate

1. Firm
2. Frost-free
3. Load-bearing
4. Free of adhesion inhibiting substances

Preparing the details

1. Any damaged areas or unevenness must be compensated with ASOCRET-M30.
2. Roughen any plastic pipes present and then thoroughly clean and degrease them with a suitable cleaner (e.g. acetone).

Usage

Application

1. Apply the waterproofing material at least 2 cm wider than the sealing collar on both sides of the pipe connection.
2. Lay ADF[®]-Rohrmanschette in the fresh layer.
3. Press the ADF[®]-Rohrmanschette into the waterproofing layer meticulously without voids or wrinkles, using a flat trowel or pressure roller.
4. Bond joint-tape edges or connections with the waterproofing material without wrinkles, covering the whole area, and overcoat after.
5. Joint-tape edges or connections to pre-formed pieces are applied with an overlap of 5 cm to 10 cm.

Storage conditions

Storage

Cool, dry, protected from sunlight. Min. 24 months in the original container.

The rights of the buyer with regard to the quality of our materials are based on our terms and conditions of sale and delivery. Our technical advice team will be happy to advise you in the case of requirements that exceed the scope of the application described here. In order to be binding, a legally binding written confirmation is required. The product description does not release the user from a duty of care. Lay a test area in the event of uncertainty. This version becomes invalid in the event of a new version being issued.