

# BLANKOL-92

Environmentally friendly release agent



Material number	Contents	Unit of quantity	Packaging	Colour
406120001	25	L	Canister	clear
406120003	1000	L	Container (IBC)	clear
406120005	210	L	Drum	clear

## Product features

Concrete release agent

## Advantages

biodegradable - proof available

## Areas of application

- As a release agent for non-absorbent formwork
- Especially suitable for steel moulds and plastic-coated large-sized moulds
- For formwork temperatures up to +90°C

## Existing test certificates

Determination of the water pollution class for self-classification

## Technical Data

### Material properties

Base material	Mineral oil
Consistency	liquid, not dilutable
Density (spec. weight)	approx. 0.82 g/cm <sup>3</sup>
Water dilutable	No

### Application

Consumption	approx. 15.00 - 50.00 g / m <sup>2</sup>
-------------	--

## BLANKOL-92

### Application technology

#### Aids/tools

- Pressure spray system
- Spray equipment

#### Manual processing

Sprayable with pressure spray device

### Substrate preparation

#### Requirement for substrate

1. Clean
2. Dry

### Usage

#### Application

Use a suitable automatic or manual spray system for application.

### Storage conditions

#### Storage

Store in a cool and dry place. Min. 24 months in the original canister. Promptly use opened canister.

### Notes

- Pre-testing is absolutely necessary!
- Observe the regulations for handling substances containing solvents; request an EU safety data sheet if necessary.
- Avoid puddle formation.
- Excessive application can cause crust formation and buildup.
- BLANKOL-92 is not dilutable with water!
- Heated formwork up to +90°C maximum!
- Welding, work with flying sparks, open flame, etc. must be avoided near the freshly sprayed, wet formwork.
- Do not use BLANKOL-92 in exterior formwork.
- Before use in a drinking water area, contact the customer and perform pretests to determine suitability.
- Expert opinion on biodegradability: Dir.Log.-No. A 174 E/93/R (Hygiene-Institut des Ruhrgebiets, Gelsenkirchen).

### Observe applicable safety data sheet!

GISCODE: BTM30

The rights of the buyer with regard to the quality of our materials are based on our terms and conditions of sale and delivery. Our technical advice team will be happy to advise you in the case of requirements that exceed the scope of the application described here. In order to be binding, a legally binding written confirmation is required. The product description does not release the user from a duty of care. Lay a test area in the event of uncertainty. This version becomes invalid in the event of a new version being issued.